

Recoding Variable Values

David Gerard

2020-10-07

Learning Objectives

- Changing the values of a variable based on its current value with `recode()`.
- Changing the values of a variable based on logical statements with `if_else()`.
- Replacing NA's with `replace_na()`.

Change variable values with `recode()`

- Variable values are sometimes uninformative. You might want to change these values before plotting or calculating summary statistics.
- E.g. the estate data in “estate.csv” at https://dcgerard.github.io/stat_412_612/data/estate.csv:

```
library(tidyverse)
estate <- read_csv(file = "https://dcgerard.github.io/stat_412_612/data/estate.csv")
```

- `estate` contains the following variables:
 - **Price**: Sales price of residence (in dollars)
 - **Area**: Finished area of residence (in square feet)
 - **Bed**: Total number of bedrooms in residence
 - **Bath**: Total number of bathrooms in residence
 - **AC**: 1 = presence of air conditioning, 0 = absence of air conditioning
 - **Garage**: Number of cars that a garage will hold
 - **Pool**: 1 = presence of a pool, 0 = absence of a pool
 - **Year**: Year property was originally constructed
 - **Quality**: Index for quality of construction. **High**, **Medium**, or **Low**.
 - **Style**: Categorical variable indicating architectural style
 - **Lot**: Lot size (in square feet)
 - **Highway**: 1 = highway adjacent, 0 = highway not adjacent.
- It would be better if we could change the 0/1 coding for **AC**, **Pool**, and **Highway** to something more informative. That way we won’t have to always look up the coding during our analysis.
- `recode()`:
 - Takes a vector as its first argument.
 - Each subsequent argument contains two values separated by an equals sign.
 - The value on the left of the equals sign is the current value inside the vector.
 - The value on the right of the equals sign is the new value for the vector.

- If the current value inside the vector is a numeric, then you need to surround its value by backticks ```>.
- It returns a vector with replaced values.

- Toy example:

```
char_vec <- c("a", "a", "b", "c", "c", "a", "b", "b", "c")
recode(char_vec,
      a = "Apple")

## [1] "Apple" "Apple" "b"       "c"       "c"       "Apple" "b"       "b"       "c"

recode(char_vec,
      b = "Banana")

## [1] "a"       "a"       "Banana" "c"       "c"       "a"       "Banana" "Banana"
## [9] "c"

recode(char_vec,
      a = "Apple",
      b = "Banana",
      c = "Carrot")

## [1] "Apple"  "Apple"  "Banana" "Carrot" "Carrot" "Apple"  "Banana" "Banana"
## [9] "Carrot"
```

- **Exercise:** In the below vector, recode "Bob" to be "Robert", "John" to be "Jonathan", and "Dave" to be "David".

```
namevec <- c("Bob", "John", "John", "John", "Dave", "Bob", "Bob", "Dave", "John")
```

- Let's use `recode()` in to change the `Quality` values in the `estate` data frame. Recall: we need to use `mutate()` to modify a variable in a data frame.

```
estate %>%
  mutate(Quality = recode(Quality,
                           High    = "Palace",
                           Medium  = "Home",
                           Low     = "Slum")) ->
  estate
glimpse(estate)

## #> #> #> #>
```

Rows: 522
Columns: 12
\$ Price <dbl> 360000, 340000, 250000, 205500, 275500, 248000, 229900, 150...
\$ Area <dbl> 3032, 2058, 1780, 1638, 2196, 1966, 2216, 1597, 1622, 1976,...
\$ Bed <dbl> 4, 4, 4, 4, 4, 3, 2, 3, 3, 7, 3, 5, 5, 3, 5, 2, 3, 4, 3,...
\$ Bath <dbl> 4, 2, 3, 2, 3, 3, 2, 1, 2, 3, 5, 4, 4, 4, 3, 5, 2, 4, 3, 3,...
\$ AC <dbl> 1, 1, 1, 1, 1, 1, 1, 0, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,...
\$ Garage <dbl> 2, 2, 2, 2, 5, 2, 1, 2, 1, 2, 3, 3, 2, 2, 2, 2, 2, 2, 2,...
\$ Pool <dbl> 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0,...
\$ Year <dbl> 1972, 1976, 1980, 1963, 1968, 1972, 1955, 1975, 1918,...

```

## $ Quality <chr> "Home", "Home", "Home", "Home", "Home", "Home", "Ho...
## $ Style    <dbl> 1, 1, 1, 1, 7, 1, 7, 1, 1, 7, 1, 7, 5, 1, 6, 1, 7, 7, 1, ...
## $ Lot      <dbl> 22221, 22912, 21345, 17342, 21786, 18902, 18639, 22112, 143...
## $ Highway <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ...

```

- Let's modify AC. We'll need backticks here since 1 and 0 are numerics.

```

estate %>%
  mutate(AC = recode(AC,
    `1` = "AC",
    `0` = "No AC")) ->
estate
glimpse(estate)

```

```

## Rows: 522
## Columns: 12
## $ Price    <dbl> 360000, 340000, 250000, 205500, 275500, 248000, 229900, 150...
## $ Area     <dbl> 3032, 2058, 1780, 1638, 2196, 1966, 2216, 1597, 1622, 1976, ...
## $ Bed       <dbl> 4, 4, 4, 4, 4, 3, 2, 3, 3, 7, 3, 5, 5, 3, 5, 2, 3, 4, 3, ...
## $ Bath      <dbl> 4, 2, 3, 2, 3, 3, 2, 1, 2, 3, 5, 4, 4, 4, 3, 5, 2, 4, 3, 3, ...
## $ AC        <chr> "AC", ...
## $ Garage    <dbl> 2, 2, 2, 2, 5, 2, 1, 2, 1, 2, 3, 3, 2, 2, 2, 2, 2, 2, 2, ...
## $ Pool      <dbl> 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ...
## $ Year      <dbl> 1972, 1976, 1980, 1963, 1968, 1972, 1972, 1955, 1975, 1918, ...
## $ Quality   <chr> "Home", "Home", "Home", "Home", "Home", "Home", "Home", ...
## $ Style     <dbl> 1, 1, 1, 1, 7, 1, 1, 1, 7, 1, 7, 5, 1, 6, 1, 7, 7, 1, ...
## $ Lot       <dbl> 22221, 22912, 21345, 17342, 21786, 18902, 18639, 22112, 143...
## $ Highway  <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ...

```

- Exercise:** Recode the Highway and Pool variables to have more informative values.

Recode with Logicals with `if_else()`

- Sometimes, it is easier to recode based on logical statements.
- For example, suppose we want to recode the “Bath” variable to have values 1, 2, 3, and >3. One way to do this would be:

```

estate %>%
  mutate(Bath = as.character(Bath),
    Bath = recode(Bath,
      `4` = ">3",
      `5` = ">3",
      `6` = ">3",
      `7` = ">3")) ->
estate_temp
glimpse(estate_temp)

```

```

## Rows: 522
## Columns: 12
## $ Price    <dbl> 360000, 340000, 250000, 205500, 275500, 248000, 229900, 150...
## $ Area     <dbl> 3032, 2058, 1780, 1638, 2196, 1966, 2216, 1597, 1622, 1976, ...

```

```

## $ Bed      <dbl> 4, 4, 4, 4, 4, 3, 2, 3, 3, 7, 3, 5, 5, 3, 5, 2, 3, 4, 3, ...
## $ Bath     <chr> ">3", "2", "3", "2", "3", "2", "1", "2", "3", ">3", ">...
## $ AC       <chr> "AC", "AC", "AC", "AC", "AC", "AC", "AC", "AC", "AC", "No A...
## $ Garage   <dbl> 2, 2, 2, 2, 5, 2, 1, 2, 1, 2, 3, 3, 2, 2, 2, 2, 2, 2, 2, ...
## $ Pool     <dbl> 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ...
## $ Year     <dbl> 1972, 1976, 1980, 1963, 1968, 1972, 1972, 1955, 1975, 1918, ...
## $ Quality  <chr> "Home", "Home", "Home", "Home", "Home", "Home", "Ho...
## $ Style    <dbl> 1, 1, 1, 1, 7, 1, 7, 1, 1, 7, 1, 7, 5, 1, 6, 1, 7, 7, 1, ...
## $ Lot      <dbl> 22221, 22912, 21345, 17342, 21786, 18902, 18639, 22112, 143...
## $ Highway  <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, ...

```

- But this is a lot of typing. But we know how to get obtain TRUE's and FALSE's based on whether a house has more than 3 bathrooms.

```

estate %>%
  mutate(Bath > 3) %>%
  select(contains("Bath")) %>%
  glimpse()

```

```

## Rows: 522
## Columns: 2
## $ Bath      <dbl> 4, 2, 3, 2, 3, 3, 2, 1, 2, 3, 5, 4, 4, 4, 3, 5, 2, 4, 3, ...
## $ `Bath > 3` <lgl> TRUE, FALSE, FALSE, FALSE, FALSE, FALSE, F...

```

- `if_else()`:
 - Takes a *logical* vector as its first argument.
 - It takes a vector that populates the TRUE values as its second argument.
 - It takes a vector that populates the FALSE values as its third argument.
 - The second and third arguments *must be the same type* (e.g. both logical, both numeric, both character, etc).
 - The second and third arguments must either be of length 1, or the same length as the logical vector.
 - It returns a vector with replaced values.

- Toy Example:

```

x <- c(1, 2, 3, 4, 5, 6, 7, 8)
if_else(x > 4, 4, x)

```

```

## [1] 1 2 3 4 4 4 4 4

```

```

if_else(x > 4, x, 4)

```

```

## [1] 4 4 4 4 5 6 7 8

```

```

if_else(x > 4, "x > 4", as.character(x))

```

```

## [1] "1"      "2"      "3"      "4"      "x > 4"  "x > 4"  "x > 4"  "x > 4"

```

```
if_else(x > 4, "x > 4", x) ## should error

## Error: `false` must be a character vector, not a double vector.
```

- **Exercise:** Why did the last `if_else()` call error?
- Let's apply `if_else()` to the `estate` data frame. Recall: we need to use `mutate()` to modify a variable in a data frame.

```
estate %>%
  mutate(Bath = if_else(Bath > 3,
    ">3",
    as.character(Bath))) ->
  estate_temp
glimpse(estate_temp)

## #> #> #> #> #>
```

Rows: 522
Columns: 12
\$ Price <dbl> 360000, 340000, 250000, 205500, 275500, 248000, 229900, 150...
\$ Area <dbl> 3032, 2058, 1780, 1638, 2196, 1966, 2216, 1597, 1622, 1976,...
\$ Bed <dbl> 4, 4, 4, 4, 4, 4, 3, 2, 3, 3, 7, 3, 5, 5, 3, 5, 2, 3, 4, 3,...
\$ Bath <chr> ">3", "2", "3", "2", "3", "2", "1", "2", "3", ">3", ">...
\$ AC <chr> "AC", "AC", "AC", "AC", "AC", "AC", "AC", "AC", "AC", "No A...
\$ Garage <dbl> 2, 2, 2, 2, 5, 2, 1, 2, 1, 2, 3, 3, 2, 2, 2, 2, 2, 2,...
\$ Pool <dbl> 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0,...
\$ Year <dbl> 1972, 1976, 1980, 1963, 1968, 1972, 1972, 1955, 1975, 1918,...
\$ Quality <chr> "Home", "Home", "Home", "Home", "Home", "Home", "Home", "Ho...
\$ Style <dbl> 1, 1, 1, 1, 7, 1, 7, 1, 1, 7, 1, 7, 5, 1, 6, 1, 7, 7, 1,...
\$ Lot <dbl> 22221, 22912, 21345, 17342, 21786, 18902, 18639, 22112, 143...
\$ Highway <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,...

- **Exercise:** Recode `Price` so that any price less than \$250,000 is just listed as "<250,000".

Dealing with NA's by `replace_na()`

- The `starwars` data frame from the `dplyr` package contains information on different characters from the `Star Wars` franchise:

```
data("starwars")
glimpse(starwars)

## #> #> #> #> #>
```

Rows: 87
Columns: 14
\$ name <chr> "Luke Skywalker", "C-3PO", "R2-D2", "Darth Vader", "Leia...
\$ height <int> 172, 167, 96, 202, 150, 178, 165, 97, 183, 182, 188, 180...
\$ mass <dbl> 77.0, 75.0, 32.0, 136.0, 49.0, 120.0, 75.0, 32.0, 84.0, ...
\$ hair_color <chr> "blond", NA, NA, "none", "brown", "brown, grey", "brown"...
\$ skin_color <chr> "fair", "gold", "white, blue", "white", "light", "light"...
\$ eye_color <chr> "blue", "yellow", "red", "yellow", "brown", "blue", "blu...
\$ birth_year <dbl> 19.0, 112.0, 33.0, 41.9, 19.0, 52.0, 47.0, NA, 24.0, 57....
\$ sex <chr> "male", "none", "male", "female", "male", "femal..."

```

## $ gender      <chr> "masculine", "masculine", "masculine", "masculine", "fem...
## $ homeworld   <chr> "Tatooine", "Tatooine", "Naboo", "Tatooine", "Alderaan",...
## $ species     <chr> "Human", "Droid", "Droid", "Human", "Human", "Human", "H...
## $ films       <list> [<"The Empire Strikes Back", "Revenge of the Sith", "Re...
## $ vehicles    <list> [<"Snowspeeder", "Imperial Speeder Bike">, <>, <>, <>, ...
## $ starships   <list> [<"X-wing", "Imperial shuttle">, <>, <>, "TIE Advanced ...

```

- The `gender` variable is missing for some individuals

```

starwars %>%
  filter(is.na(gender)) %>%
  select(name, gender)

```

```

## # A tibble: 4 x 2
##   name      gender
##   <chr>     <chr>
## 1 Ric Olié  <NA>
## 2 Quarsh Panaka <NA>
## 3 Sly Moore <NA>
## 4 Captain Phasma <NA>

```

- But because programmers typically remove NA's, it might be reasonable to change this to something else like "other".
- `replace_na()`
 - Takes a vector as its first argument.
 - The second argument is the value with which to replace all NA's.
 - It returns a vector with the NA's replaced.
- Toy example:

```

x <- c("This", "is", "a", NA, NA, "vector")
replace_na(x, "foo")

## [1] "This"    "is"      "a"       "foo"     "foo"     "vector"

```

- Let's replace the NA's in the `gender` variable in the `starwars` data frame. Recall: we need to use `mutate()` to modify a variable in a data frame.

```

starwars %>%
  mutate(gender = replace_na(gender, "other")) %>%
  select(name, gender) %>%
  glimpse()

```

```

## Rows: 87
## Columns: 2
## $ name    <chr> "Luke Skywalker", "C-3PO", "R2-D2", "Darth Vader", "Leia Org...
## $ gender   <chr> "masculine", "masculine", "masculine", "masculine", "feminin...

```

- Exercise:** In the `starwars` data frame, replace the NA's in `hair_color` with "bald".